



Email: info@fixtech.com.au

# **SAFETY DATA SHEET**

### Fix8 Silicone Aluminium & Translucent

#### 1. Identification

#### 1.1 Identification of the substance or preparation:

Product Name: Fix8 Aluminium, Fix8 Translucent

#### 1.2 Use of substance or preparation:

Adhesive Sealant

#### 1.3 Company undertaking identification:

Fixtech Pty Ltd – Fixtech Marine Solutions Unit 1/20
Molandinar Overaland 4214

Molendinar, Queensland 4214 Tel: +61 7 5530 1099

Fax: +61 7 5530 1322 Email: info@fixtech.com.au

#### 1.4 Emergency telephone:

+61 7 5530 1099

#### 2. Composition/information on ingredients

Hazardous Ingredients	CAS No.	Conc. In %
Hydroxy-terminated dimethyl siloxane	63148-60-7	59.5-89.5%
Methyltris(methylethylketoxime)silane	22984-54-9	< 10%
Vinyltris(methyethylketoxime)silane	2224-33-1	< 10%
Fumed silica	10279-57-9	< 10%
Functional silica	919-30-2; 2530-87-2; 2530-83-8	< 1%
Organometalic compound	77-58-7; 3648-18-8; 78-04-6	< 0.05%
Hydrotreated petroleum distillates	8012-95-1	10-20%
Titanium (IV) oxide	13463-67-7	0.5%





Email: info@fixtech.com.au

# **SAFETY DATA SHEET**

### Fix8 Silicone Aluminium & Translucent

#### 3. Hazardous identification

Hazard category	Hazard statement	Signal word	Symbol Exclamation Mark
4	H302 Harmful if swallowed		
2	H315 Cause skin irritation		•
2A	H319 Cause serious eye irritation	Warning	!
A	H332 Harmful if inhaled		

#### 4. First aid measures

#### 4.1 After inhalation:

- Remove the victim to fresh air
- Respiratory difficulties: consult a doctor/ seek medical advice

#### 4.2 Skin contact:

- Rinse with water
- Soap may be used
- Seek medical advice if irritation persists

#### 4.3 Eve contact:

- Immediately flush with water for 15 minutes
- Seek medical advice if irritation persists

#### 4.4 After ingestion:

- Rinse mouth with water
- Seek medical advice

#### 5. Fire fighting measures

**5.1 Flash point:** Not applicable

**5.2 Auto ignition Temperature:** Not determined

**5.3 Flammability limits (in air):** Not determined





Email: info@fixtech.com.au

# **SAFETY DATA SHEET**

### Fix8 Silicone Aluminium & Translucent

**5.4 Extinguishing media:** On large fires use dry chemical, foam or water spray. On small fires

use carbon dioxide (CO2), dry chemical or water spray. Water can

be used to cool fire-exposed containers.

**5.5 Fire fighting measures:** Self contained breathing apparatus and protective clothing should

be worn in fighting large fires involving chemicals. Determine the

need to evacuate or isolate the area according to your local

emergency plan. Use water spray to keep fire exposed containers

cool.

**5.6 Unusual Fire Hazards:** None

#### **Hazardous decomposition of products:**

Thermal breakdown of this product during or very high heat conditions may evolve the following hazardous decomposition products: Carbon Oxides and traces of incompletely burnt Carbon compounds. Nitrogen Oxides, Silicone Dioxide. Formaldehyde, Metal Oxides, Sulfur Oxides, Iodine compound and Quartz

#### 6. Accidental release measures

#### 6.1 Containment/clean up:

Observe all personal protection and equipment recommendations described in sections 5 and 8. Wipe up or clean up and contain for disposal. Clean area as appropriate to prevent slip hazards. Final cleaning may require the use of solvents and/or detergents. Dispose of waste as spontaneous heating may occur. Local, State and Federal laws and regulations may apply to releases and disposal of waste material, as well as the material used in the cleanup of releases. You will need to determine the applicable regulations.

Sections 13 and 15 of this MSDS provide information regarding certain federal and state regulations.

#### 7. Handling and storage

Note: See section 8 for Personal Protective Equipment.

#### 7.1 Handling:

- Observe normal hygiene standards
- Do not discharge waste into drains

Use with adequate ventilation. Product produces flammable Methyl Alcohol when exposed to water or humid air. Provide ventilation during use to control exposure to within Section 8

Page 3





Email: info@fixtech.com.au

## SAFETY DATA SHEET

### Fix8 Silicone Aluminium & Translucent

guidelines or use with air supplied or self-contained breathing apparatus. Avoid eye contact. Avoid breathing vapour.

Keep container closed. Do not take internally

use reasonable care and store away from oxidizing materials. Keep container closed and store away from moisture.

#### 7.2 Storage:

- Keep container tightly closed
- Keep out of direct sunlight
- Store in a dry area
- Keep away from ignition and heat sources

Storage temperature : Room temperature

#### 8. Exposure controls/personal protection

#### **8.1 Personal Protective Equipment:**

Eyes: Use proper protection – safety glasses as a minimum Skin: Washing at breaks and end of shift is adequate

Suitable Gloves: No special protection needed

Inhalation: Use respiratory protection unless adequate local exhaust ventilation

is provided or air sampling data shows exposure to be within recommended guidelines. OH&S/Industrial hygiene personnel can

assist in judging the adequacy of existing controls.

Suitable Respirator: General and local exhaust ventilation is recommended to maintain

vapour exposures below recommended limits. Where

concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OH&S/OHSA respirator regulations

(29 CFR 1910.134). Use NIOHS/MSHA/OH&S approved respirators

#### 9. Physical and Chemical Properties

#### 9.1 General information:

Physical Form: Paste

Colour: See product information

Odour: Odourless Specific Gravity @ 25°C: 0.97

Viscosity: Not Determined

Page 4

SDS: Fix8 Silicone SDS Established: March 2015 SDS Revised: an.01/08/2017





Email: info@fixtech.com.au

## SAFETY DATA SHEET

## Fix8 Silicone Aluminium & Translucent

Freezing/Melting point:

Boiling point:

Vapour pressure @ 25°C:

Vapour density:

Solubility in water:

PH:

Not Determined

Note: the above information is not intended for use in preparing product specifications

#### 10. Stability and reactivity

10.1 Stability

Chemical Stability: Stable

Hazardous Polymerization: Will not occur

10.2 Reactivity:

Conditions to avoid: None

Materials to Avoid: Oxidizing material can cause a reaction. Water, moisture or

humid air can cause hazardous vapours to form as described

in Section 8

#### 11. Toxilogical information

**11.1 Special hazard information on components**: No known applicable information

#### 12. Effects on the environment

**12.1 Environmental fate and distribution:** Solid material, insoluble in water. No adverse

affects are predicted.

**12.2** Environmental effects: No adverse effects on aquatic organisms are

predicted.

**Bio-accumulation:** No bio-accumulation potential

12.3 Fate and effects in waste water treatment plants:

No adverse affects are predicted on bacteria.

This table is adapted from "Environmental Toxicology and Risk Assessment" ASTM STP 1179,

Page 5

SDS: Fix8 Silicone SDS Established: March 2015 SDS Revised: an.01/08/2017





Email: info@fixtech.com.au

## **SAFETY DATA SHEET**

### Fix8 Silicone Aluminium & Translucent

page 34, 1993

This table can be used to classify the Ecotoxicity of this product when Ecotoxicity data is listed.

#### 13. Disposal considerations

#### 13.1 RCRA hazard class (40 CFR 261):

When a decision is made to discard the material, as received, is it classified as a hazardous waste?

No

State or local laws may impose additional regulatory requirements regarding disposal

#### 14. Transport information

#### 14.1 Classification of the substance in accordance with UN recommendations

UN Number : Not Applicable

CLASS : - PACKAGING GROUP : -

14.2 ADR (transport by road)

CLASS : Not subject

PACKAGING GROUP : CLASSIFICATION CODE : DANGER LABEL TANKS : DANGER LABEL PACKAGES : PROPER SHIPPING NAME : -

#### 15. Transport information - continued

#### 14.3 RID (transport by rail)

CLASS : Not subject

PACKAGING GROUP : CLASSIFICATION CODE : DANGER LABEL TANKS : DANGER LABEL PACKAGES : PROPER SHIPPING NAME : -

#### 14.4 ADNR (transport by inland waterways)

SDS: Fix8 Silicone SDS Established: March 2015 SDS Revised: an.01/08/2017





Email: info@fixtech.com.au

## SAFETY DATA SHEET

### Fix8 Silicone Aluminium & Translucent

CLASS : Not subject

PACKAGING GROUP : CLASSIFICATION CODE : DANGER LABEL TANKS : DANGER LABEL PACKAGES : -

14.5 IMDG (maritime transport)

CLASS : Not subject

SUB RISKS : PACKAGING GROUP : MFAG : EMS : MARINE POLLUTANT : -

14.6 ICAO (air freight)

CLASS : Not Subject

SUB RISKS : PACKAGING GROUP : PACKAGING INSTRUCTIONS PASSENGER AIRCRAFT : PACKAGING INSTRUCTIONS CARGO AIRCRAFT : PROPER SHIPPING NAME : -

**14.7 Special precautions:** Keep separated from foodstuffs

#### 16. Other information

This data completes the technical datasheet for use, but does not replace it. The data given here is based on current knowledge and experience. The purpose of this safety data sheet is to describe the products in terms of their safety requirements.

The data does not signify any warranty with regards to the products properties.